



Connecting boxes
ITplus®Standard, FLF

Connecting box ITplus® RJ45 Cat.6A, unshielded

>20 overplugging cycles, >1,000 insertion/withdrawal cycles, captive dust protection, Keystone, straight outlet, installation depth 39 mm.

1-way with reserve slot

2-way

Connecting box ITplus® RJ45 Cat.6A, shielded

>20 overplugging cycles, >1,000 insertion/withdrawal cycles, captive dust protection, Keystone, straight outlet, installation depth 39 mm.

1-way with reserve slot

2-way

Connecting box, non-equipped for ITplus® systems

2-way

	Complete apparatuses flush mounted PMI 58 mm white	Complete apparatuses surface-mounted AP x white	Complete apparatuses parapet duct IK 63 mm white	Complete apparatuses mounting FLF white
	COU-81,301-61 979 231 008	COU-81,101-61 979 031 008	COU-81,401-61 979 431 008	COU-81 501-61 979 631 008
	COU-81,302-61 979 232 008	COU-81,102-61 979 032 008	COU-81,402-61 979 432 008	COU-81,502-61 979 632 008
	COS-81,301-61 979 201 008	COS-81 101-61 979 001 008	COS-81,401-61 979 401 008	COS-81 501-61 979 601 008
	COS-81 302-61 979 202 008	COS-81,102-61 979 002 008	COS-81,402-61 979 402 008	COS-81,502-61 979 602 008
	COU-81,300-61 979 230 008	COU-81,100-61 979 030 008	COU-81,400-61 979 430 008	COU-81,500-61 979 630 008

**Connecting boxes ITplus®
EDIZIOdue**

Connecting box ITplus® RJ45 Cat.6A, unshielded

>20 overplugging cycles, >1,000 insertion/withdrawal cycles, captive dust protection, Keystone, flat outlet, installation depth 39 mm.

1-way with reserve slot

Complete apparatuses flush mounted FML, white



COU-83,341-61
879 280 000

Complete apparatuses surface-mounted FX 54, white



COU-83,141-61
879 080 000

Complete apparatuses parapet duct FKE



COU-83 441-61
879 480 000

2-way

COU-83,342-61
879 282 000

COU-83,142-61
879 081 000

COU-83,442-61
879 481 000

Connecting box ITplus® RJ45 Cat.6A, shielded

>20 overplugging cycles, >1,000 insertion/withdrawal cycles, captive dust protection, Keystone, flat outlet, installation depth 39 mm.

1-way with reserve slot



COS-83,341-61
879 260 000



COS-83,141-61
879 060 000



COS-83,441-61
879 460 000

2-way

COS-83,342-61
879 262 000

COS-83,142-61
879 061 000

COS-83,442-61
879 461 000

Connecting box, non-equipped for ITplus® systems, flat outlet

2-way



COU-83,340-61
878 260 000



COU-83,140-61
878 060 000



COU-83,440-61
878 487 000

Connecting box, non-equipped for ITplus® systems

2-way



COU-83,300-61
878 270 000



COU-83,100-61
878 070 000



COU-83,400-61
878 477 000

Jacks ITplus® (see also page 8)



Jack ITplus® RJ45 Cat.6A 10G, unshielded
COU-90 010-61 966 702 766



Jack ITplus® RJ45 Cat.6A 10G, shielded
COS-90 010-61 966 702 866



Jack ITplus® RJ11 screw connection
SOH-12 101 977 801 048



Dummy insert ITplus®
COU-93 001-61 966 733 808

COZ-06 902 966 799 966

A4 label sheet for ITplus® connecting boxes

Paper quality 60 g, with 120 perforated and self-adhesive designation labels. Template can be downloaded on Internet at no cost.



COZ-06 906 966 732 066

AP connection box, 6-way

Keystone, sheet steel, white RAL 9010 for optional equipping with ITplus® Keystone inserts. Dimensions 38x115x165 mm. Rear side with 3 cable inlets, one each on left, right and bottom. Including 4 covers for reserve inlets.

