

LANmark-6 S-FTP LSZH 1000m reel

Nexans ref.: N100.631

- Complies to latest Cat 6 standards
- Supports Class E applications
- Central cross member maintains geometry and performance
- Tested up to 350MHz

Description

Application

LANmark-6 cable is the ultimate solution for a future proof network. It is specifically designed to support the exacting requirements for tomorrow's protocols, yet is fully backwards compatible with today's needs. It is the recommended cable for all forthcoming installations.

- 10baseT Ethernet
- 100baseTX Fast Ethernet
- 1000baseTX Gigabit Ethernet
- 155 MBit ATM
- 622 MBit ATM
- 1.2 Gbit ATM
- future class E applications

LANmark-6 is independently verified to exceed the requirements of the ISO/IEC 11801:2002 Category 6 requirements.

Performance

Tested to 350 MHz and with guaranteed performance to 250 MHz, Nexans LANmark-6 cables provide guaranteed headroom and bandwidth over and above the requirements of all international, european and american cable standards, including ISO/IEC 11801:2002, IEC 61156-5, EN 50173, EN 50288, TIA/EIA 568-B.2-1.

Installation

LANmark-6 is installed in exactly the same way as Category 5 cables. The C³ central cross member reduces the risk of crushing and kinking.

Guarantees


Nexans LANmark-6 cable is covered by the guarantee that it is Category 6 and by a parts and labour warranty as described in the Nexans Certified System Warranty.




LANmark-6

Standards


International EN 50288;IEC 61156-5;ISO/IEC 11801
National TIA/EIA-568-B.2-1




Operating temperature, range
-10 .. 40 °C



Ambient install temp, range (°C)
-10 .. 50 °C



Min. static operating bending rad.
31.0 mm



Laying operation bending rad.
62.0 mm




Flame retardant
IEC 60332-1


LANmark-6 S-FTP LSZH 1000m reel

Contact


Cabling Solutions
Alsebergsesteenweg 2, b3
B-1501 Buizingen
Belgium
Phone: +32 2 363 38 00
info.ncs@nexans.com




Operating temperature,
range
-10 .. 40 °C



Ambient install temp, range
(°C)
-10 .. 50 °C



Min. static operating bending
rad.
31.0 mm



Laying operation bending
rad.
62.0 mm



Flame retardant
IEC 60332-1

LANmark-6 S-FTP LSZH 1000m reel

Nexans ref.: N100.631

Characteristics

Construction characteristics

Type of cable	S-FTP
Outer sheath	LSZH
Colour	Orange

Dimensional characteristics

Diameter over insulation	1.13 mm
Nominal outer diameter (mm)	7.1 mm
Approximate weight (kg/km)	58 kg/km
Conductor cross-section (AWG)	24

Electrical characteristics

Mutual capacitance (nF/km)	56 nF/km
Max. DC-resistance of the conductor at 20° C	70 Ohm/km
Characteristic impedance	100 Ohm
Transfer impedance	20

Transmission characteristics

Attenuation Crosstalk Ratio, 250MHz	5.5 dB/100m
Skew	30 ns/100m
Velocity of propagation	68.0 %
Coupling attenuation at 30 MHz	80 dB
Propagation delay, max. 100 MHz	536 ns/100m

Usage characteristics

Packaging	Reel
Length (m)	1000 m
Operating temperature, range	-10 .. 40 °C
Ambient installation temperature, range (°C)	-10 .. 50 °C
Minimum static operating bending radius	31.0 mm
Laying operation bending radius	62.0 mm
Category	Cat. 6
Flame retardant	IEC 60332-1

Electrical Performance

All values are specified at 20°C

Frequency	Attenuation dB/100m	NEXT dB	ACR dB/100m	PSNEXT(*) dB	ELFEXT dB/100m	PSELFEXT dB/100m	RL dB
1	2.0	74.3	72.3	72.3	70.0	67.0	20.0
4	3.8	65.3	61.5	63.3	58.0	55.0	23.0
10	6.0	59.3	53.3	57.3	50.0	47.0	25.0
16	7.6	56.2	48.6	54.3	45.9	42.9	25.0
20	8.5	54.8	46.3	52.8	44.0	41.0	25.0
31.25	10.7	51.9	41.2	49.9	40.5	37.5	23.6
62.5	15.4	47.4	32.0	45.4	34.1	31.1	21.5
100	19.8	44.3	24.5	42.3	30.0	27.0	20.1
155	25.2	41.4	16.2	39.5	26.2	23.2	18.8

LANmark-6 S-FTP LSZH 1000m reel

200	29.0	39.8	10.8	37.8	24.0	21.0	18.0
250	32.8	38.3	5.5	36.3	22.0	19.0	17.3
300	36.4	37.1	1.5	35.2	20.5	17.5	16.8
350	39.8	36.1	-	34.2	19.1	16.1	14.1

(*) Dual cable versions additionally comply to the additional PSNEXT requirements for multi-unit cables as specified in the relevant TIA and IEC cable standards.